



MODERN SPECIALTIES IN SYNTHETIC AND PLASTIC INKS

Rondeau 1200. Ramos Mejía, Buenos Aires, Argentina.

Phone: 4654-0060 **Fax:** 4656-1098 **E-Mail:** laboratorio@pintesint.com

www.pintesint.com

TINTA ÁLCALI SOLUBLE AZUL **(Blue Alkali Soluble Ink)** **Code ID. 4700**

This ink has been formulated for the printing of printed circuit boards. It is resistant to iron perchloride. It is recommended mesh 77 or 90 #, let dry before attacking.

DILUTION

Reduced with Retardante 169 (Retardant 169 - Code 9606).

REMOVAL

It is removed with a 10% aqueous solution of sodium hydroxide (Caustic Soda).

COLOUR

Blue Identifier

APPLICATION

On Cooper

IMPORTANT NOTE

- I. The inks formulated by Pintesint SAICyF must be used exclusively with the solvents and the complementary products that it manufactures for that purpose. Due to the diversity of products in the market, the company is not responsible for the use of the same from another source.
- II. The suggestions and data of this literature were elaborated in good faith, to guide the user. We recall the importance of checking the adaptability of inks and complementary products by testing before starting production. Due to the fact that the conditions of use of the products are not under our control, the present does not constitute a guarantee on the work to be done.