



MODERN SPECIALTIES IN SYNTHETIC AND PLASTIC INKS

Rondeau 1200. Ramos Mejía, Buenos Aires, Argentina.

Phone: 4654-0060 **Fax:** 4656-1098 **E-Mail:** laboratorio@pintesint.com

www.pintesint.com

**EVAFLEX
SERIE 5700**

Satin finish paint, good hiding power, highly flexible and good resistance to abrasion.

APPLICATIONS

It is an ink formulated for coated or laminated fabrics, used in the manufacture of bags, coated tarpaulins and other sporting goods. It is also recommended for nylon, rubber, EVA foam, among others.

In order to increase its hiding power, it is recommended to use it undiluted, otherwise use Reductor vinílico /Vinyl reducer (Code 9602) or Retardador vinílico / Vinyl retarder (Code 9604).

The cleaning of the work elements is done with Vinílico de Limpieza/ Vinylic for cleaning (Code 9600).

DRYING

Depending on the environmental conditions, its drying is produced by evaporation in a period that oscillates between 10 and 30 minutes.

Printing at a temperature greater than 20 ° C (68 ° F) is recommended. Because it gels at low temperatures.

RANGE OF COLOURS

Code	Description
5710	White
5720	Yellow Lemon
5723	Yellow Chrome
5740	Colourless
5752	Red
5754	Magenta
5760	Green
5770	Royal Blue
5772	Marine Blue
5790	Black

IMPORTANT NOTE

- I. The inks formulated by Pintesint SAICYF must be used exclusively with the solvents and the complementary products that it manufactures for that purpose. Due to the diversity of products in the market, the company is not responsible for the use of the same from another source.
- II. The suggestions and data of this literature were elaborated in good faith, to guide the user. We recall the importance of checking the adaptability of inks and complementary products by testing before starting production. Due to the fact that the conditions of use of the products are not under our control, the present does not constitute a guarantee on the work to be done.